



## YOUR COFFEE EXPERIENCE

# DISKO

Automatic tamper standalone

**Disko takes care of tamping.**

**Be fast. Achieve consistency. Protect your arms.**

- **High tamping speed:** just 0.9 seconds. Your workflow gains speed.
- **Automatic portafilter recognition** (thanks to metallic reader sensor): enhance speed and safety during workflow.
- **Pressing force choice:** Always get an even and consistent tamping, adjustable from a range from 10 to 30 kilos.
- **Compact and modern design:** it fits easily in every barista's workspace.
- Possibility to **select between single or double tamping** (sequential): choose the tamping profile your prefer.
- **High- speed maintenance:** the "Clean mode" enables to lower and (possibly) remove the tamping disk.
- **Metal Body** combined with Rubbered feet: ensuring solidity and stability on the counter.
- **Universal fork**, easily adjustable in height, compatible with any kind of filterholder (single/double/naked).
- **Available tamper diameters:** 53 / 54,3 / 57 / 58 mm\*.



#### Cleaning kit included:

- **Allen spanner** for quick disassembly of the pressing disc.
- **Brush** for polish hard-to-reach places.

\*Standard configuration is available in 58 mm.  
53 / 54,3 / 57 mm available as spare parts.



SPECIFICATIONS		DISKO
Tamper specification	Force adjustment	from 10 - 30 kg
	Tamping speed	0.9 sec. (1 tamp)
		1.5 sec. (2 tamps)
	Sequential tamping	Yes (up to 2)
	(Available) Tamper diameter	53 / 54.3 / 57 / 58 mm *
	Fork adjustable in height	Yes (screw in cleaning kit)
	Portafilter compatibility	1-2-Naked portafilters
Usability specifications	Display	LED
	Device activation	Metallic sensor
	Cleaning mode	Yes (from display)
	Removable tamping disk	Yes (by screw)
Techincal specifications	Net weighth	5.7 kg
	Dimensions (DxWxH)	11 X 22.4 X 25.6 cm
	Plug type	All
	Input	50/60 Hz
	Power	100 W
Finishing specifications	Available colours	Matt black (body) & Matt Grey (base)
	Material	Body - Satin Aluminum
		Fork - Chromed aluminium
		Base - Rubber
LIST PRICE		599 €

\* Standard configuration is available in 58 mm.  
53 / 54,3 / 57 mm available as spare parts.